



RUNWAY VISUAL RANGE (RVR) MAST

DESCRIPTION

Our RVR mast is manufactured in the UK from fibreglass, finished with a UV resistant gel coat. It is supplied with a galvanised steel hinged base plate (180 x 180mm) with associated fixings. The 50mm stainless steel top cap is used to affix your RVR equipment.

FEATURES

- » Non-Conductive
- » Environmentally Durable
- » Frangible - ICAO/FAA Compliant
- » Easy Maintenance
- » UV and Salt Resistant Red/White Banding
- » Adjustable to Fit Any Manufacturer Sensor
- » 10 Year Warranty

CERTIFICATION

- » FAA L-891 Low Impact Resistant Structures (AC150/5345-45C)
- » ICAO Doc 9157 AN/901 ADM Part 6 - Frangibility
- » ISO 9001:2015

SPECIFICATION

Mast Height (m)	2 - 4.5
Mast Diameter Ø (mm)	125
Ground Plate Dimensions (mm)	180 x 180
Top Cap Diameter Ø (mm)	50
Top Cap Length (mm)	450
Top Cap Material	Powder Coated Stainless Steel
Ground Rod Diameter Ø (mm)	16
Ground Rod Length (mm)	500
Hollow Spigot Dimension (mm)	50 x 450